



SHIELDCOAT PTY LTD
Unit 2/1075 Beaudesert Rd, Archerfield Q 4108
Phone: (07) 3274 6911 Fax: (07) 3274 6414
Email: info@shieldcoat.com.au Web: www.shieldcoat.com.au

Application Method: **MOULDSHIELD C***
Multipurpose heavy duty cleaner

NOTE: For applications where roof to be painted is used for collecting drinking water, ensure at least seven (7) days or the first rain before reconnecting downpipes.



STEPS:

- For cleaning floors, roofs and walls use at a dilution of 1 part **Mouldshield C** in 20-40 parts water. I.e. up to 50ml per litre of warm water.
- To remove heavy soil and fungal growth use at a dilution of 1 part **Mouldshield C** to 5 parts water then soak until the deposit has softened, brush and rinse with clean water.
- For industrial uses **Mouldshield C** should be first used at a dilution of 1 part Mouldshield C in 20 parts water. This concentration can be varied to suit the conditions.
- Apply by broom or backpack pressure spray to surfaces. Improved results may be expected from longer contact times except on soft metals. Rinse thoroughly with fresh water after cleaning.

* Before using this product consult the product MSDS

Shieldcoat is firmly committed to providing product and service of the highest quality and consistency.

Last modified on: 31/12/02

DISCLAIMER

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.