



Roofbond Coating System

Roofbond Coating System

Shieldcoat's Roofbond coating systems are manufactured to withstand Australia's unique and demanding climate, using an all acrylic binder specifically recommended for roof refurbishment applications. Shieldcoat has chosen the best resin available on the market for this product. The criteria for Shieldcoat's choice is based on the resin's characteristics including durability, wet adhesion properties, gloss retention, low dirt pick up, low water sensitivity and through dry capabilities.

The resin chosen for the system is based on a highly UV resistant pure acrylic technology, which has been an industry bench mark for adhesion, gloss and colour retention for over 30 years. Its durability and performance have been proven over many harsh Australian and in particular many harsh Queensland seasons. Whilst its cost is premium, it will always remain the choice because of its quality and consistency.

Shieldcoat's commitment to consistent quality means that even the colours used to make Roofbond products are produced in the factory to our own rigid requirements. The pigments used have

been chosen for their durability and all are listed as 8 on a scale of 1-8 (Ratings for Xenotest exposure. Grading: 1=Poor; 8=Excellent). This control over the entire paint production process means the ability to produce colours specific to the customer's requirement, even to the levels of gloss where required.

No unnecessary fillers or extenders are added to the product, thus ensuring the best gloss finish available and the highest resin ratio of any like manufacturer. Simply put, all the raw materials used to produce one bucket of Roofbond are the highest quality products available on the market today.

- ✦ EXCELLENT EXTERIOR DURABILITY
- ✦ HIGH GLOSS LEVEL
- ✦ FAST HARDNESS DEVELOPMENT
- ✦ SUPERIOR COVERAGE/HIDE
- ✦ GOOD WATER RESISTANCE
- ✦ MOULD AND LICHEN RESISTANT
- ✦ SAFE FOR COLLECTING DRINKING WATER.
(LEAVE 7DAYS OR UNTIL AFTER THE FIRST RAIN)

