



# Product Information Sheet



Sheet Number: **0032**

Rev 22-11-06

## COVERCOAT W Stencilshield Sealer Urethane/ Acrylic water based sealer

**Covercoat W** is a urethane and acrylic blended water based sealer for protecting Stencilshield coatings. Covercoat W has a low odour and is very durable. Applied by nap roller or airless spray with 517 tip.

**General Application Guide:** Apply one coat of Covercoat W in clear by nap roller the day after Stencilshield has been applied and stencil patten or tape has been removed and discarded.

**Notes:** Covercoat W should not be applied late in the day or when moisture is present in the air or on the surface. Covercoat W can be reapplied in approximately 2 years to maintain the Stencilshield surface. Simply clean by light water blasting allow to dry and apply one more coat of Covercoat W.

### Specifications:

(all dry times are considered at 25° C and at 50% humidity)

#### Covercoat W:

**Surface Dry:** 2-4 hours

**Top Coat:** 12 hours

**Hard Dry:** 3 -5 days

**Wet Film Thickness:** Approx. 100 microns

**Dry Film Thickness:** Approx. 50 microns

**Thinning:** No thinning required normally. If desired thin with water sparingly.

**Clean Up:** Clean up with water



Top Picture: Covercoat W applied to Stencilshield with airless spray and 517 tip.

Bottom Picture: Covercoat W applied to Stencilshield.

Products come in 15 litre pails.

**See MSDS for safety information**

### Features:

ATTAR anti-slip tested



Chemical Resistant Clear Sealer



Flexible



Easy To Apply



Durable



Pre Mixed



Resists marking from hot tires



### Benefits:

Low Risk Of Slipping



Clean up easy



Allows for some substrate move-



Nap Rolled or Airless Sprayed



Lasts for Years



Stirring only required



More eye pleasing



**Notes:** There are many substrates on the market. Please consult Shieldcoast for further information regarding applications not on this sheet.